



■ Depósitos de membrana fabricada en EPDM, atóxica e intercambiable, especial para uso alimentario y circuitos de calefacción. Estan construidos en chapa de acero embutido con acabado fosfatado pintado y secado.

Válvula superior de latón.

Pintura exterior en poliuretano.

Temperatura máxima de servicio: de -5°C hasta 100°C.

Los acumuladores de más de 100 litros (incluido) se suministran de serie con manómetro para fácil lectura de la presión.

■ Membrane tanks manufactured with EPDM membrane, non-toxic and interchangeable, especially for food use and hot water circuits. They're constructed of pressed steel, painted with exterior trim drying and phosphate.

Top valve in brass.

Polyurethane exterior paint.

Maximum temperature: -5°C to +100°C.

All tank with more than 100 liters (included) are supplied, as standard, with pressure gauge for easy pressure reading.

Tipo Type	Capacidad Capacity	Presión Máx Max. pressure	Dimensions		Salida Outlet	Figura Figure	Peso Weight	Volumen Volume
			A mm	B mm				
EVO 8 EXP	8 lts	10 bar	220	320	1"	A	2,9 Kgs	0,016 m3
EVO 12 EXP	12 lts		220	380	1"	A	3,8 Kgs	0,018 m3
EVO 19 EXP	19 lts		280	430	1"	A	4 Kgs	0,034 m3
EVO 24 EXP	24 lts		280	470	1"	A	4,5 Kgs	0,037 m3
EVO 35 EXP	35 lts		380	470	1"	A	7,5 Kgs	0,068 m3
EVO 50 EXP	50 lts		380	560	1"	A	8,5 Kgs	0,081 m3
EVO 50-16 EXP	50 lts	16 bar	380	580	1"	A	14 Kgs	0,084 m3
EVO 50 VER	50 lts	10 bar	380	750	1"	B	11 Kgs	0,108 m3
EVO 80 VER	80 lts		430	960	1"	B	17 Kgs	0,161 m3
EVO 100 VER	100 lts		460	990	1"	B	18 Kgs	0,209 m3
EVO 150 VER	150 lts		500	1100	1"	B	29 Kgs	0,280 m3
EVO 200 VER	200 lts		590	1120	1 1/4"	B	38 Kgs	0,390 m3
EVO 300 VER	300 lts		640	1230	1 1/4"	B	45 Kgs	0,504 m3
EVO 500 VER	500 lts		750	1550	1 1/4"	B	75 Kgs	0,872 m3
EVO 750 VER	750 lts		750	1950	2"	B	110 Kgs	1,248 m3
EVO 1000 VER	1000 lts		800	2180	2"	B	155 Kgs	1,408 m3
EVO 1500 VER	1500 lts		960	2380	2"	B	230 Kgs	2,212 m3
EVO 24 HOR	24 lts	10 bar	470	280	1"	C	4 Kgs	0,037 m3
EVO 50 HOR	50 lts		620	380	1"	C	10,5 Kgs	0,084 m3
EVO 80 HOR	80 lts		720	430	1"	C	17 Kgs	0,133 m3
EVO 100 HOR	100 lts		800	460	1"	C	23 Kgs	0,169 m3